

# MOBILUX

## BATTERY FREEZER W. TRICYCLE

Combi version of freezer and cooler. The Mobilux 12 V freezer or cooler is the right choice if you need mobility or don't have power available. It will help you to sell your ice cream, frozen foods or cold drinks in places, where this normally would not be possible as it can be supplied and installed on a tricycle. It works with an input of 230 volt/ 110 volt to a charger, which supplies a 12 volt gel battery. Once loaded, the battery will run a 12 volt compressor. The battery and compressor are both well hidden inside the motor compartment.



TRICYCLE FOR MOBILUX 11



MOBILUX 11 FREEZER WITH SCOOP CONTAINER

## FEATURES

- Run time 8-10 hours as a freezer, and up to 24 hours as a cooler
- Charger with 110 / 230 volt input and 12 volt output
- 12 volt battery
- Flat solid sliding lid
- Lock
- Options:
  - Tricycle
  - Standard baskets or scoop baskets
  - Dividers
  - Thermometer
  - Graphics (minimum quantity required)



CONTROL PANEL

	MOBILUX 11	MOBILUX 21
<b>CLIMATE CLASS</b>		
	B (former *4*)	B (former *4*)
<b>VOLUME</b>		
Gross volume, litres	144	249
Net volume, litres	117	206
<b>TEMPERATURE</b>		
Ambient temperature range, deg. C	16 to +30	+16 to +30
Temperature range inside unit, deg. C, freezer / cooler	-18 or +4	-18 or +4
<b>COOLING DATA</b>		
Refrigerant	R290	R290
Refrigerant amount	71	93
Type of cooling	Static	Static
Type of defrost	Manual	Manual
<b>ENERGY</b>		
Energy consumption / 24 h kwh at 30 deg. C	0,9	1,2
AE- Annual Energy consumption , kwh	329	438
EEL- Energy Efficiency Index	n/a	n/a
EC-Energy Class	n/a	n/a
Input power (watt)	98	110
<b>ELECTRICAL DATA</b>		
Power	220-240 v/50Hz	220-240 v/50Hz
Power 110volt / 60 hz	Optional	Optional
Current consumption (ampere)	4	4
<b>DIMENSIONS</b>		
External dimensions (wxdxh)	724*654*916	1054*654*916
Internal dimensions (wxdxh)	520*450*686	850*450*686
Insulation (mm)	100	100
<b>STANDARD</b>		
Outer cabinet	Galvaniz. Steel	Galvaniz. Steel
Inner cabinet	painted steel	painted steel
Insulation	Polyurethane	Polyurethane
Thermostat	Mechanical	Mechanical
Castors	incl	incl
Lock	incl	incl
<b>OPTIONS</b>		
Max. number of baskets	1	2
Scoop baskets	Optional	Optional
Dividers	Optional	Optional
Castors w. brakes	Optional	Optional
Thermometer	Optional	Optional
Internal light	n/a	n/a
Graphics	Optional	Optional
Other Data		
CE (EU) / UL (USA)	CE	CE
<b>WEIGHT</b>		
Net weight, kg	55	68
Gross weight, kg	62	75
<b>SHIPPING</b>		
20' cont. Capacity	42	30
40' cont. Capacity	90	64
Standard Trailer capacity	102	74
<b>TRICYCLE</b>		
Dimensions of packaging		600*800*1500
Gross Weight, kg		30
Dimensions without packaging		2100*900*1180
Handbrake		Yes
Internal brake		Yes
Internal gears, ( pcs)		3

\*) Climate class 4 has been changed into Climate class A according to the new EU regulation.

\*) Climate class 7 has been changed into Climate class B according to the new EU regulation.

\*) Climate class 5 has been changed into Climate class C according to the new EU regulation.

\*FOR DIMENSIONS SEE PAGE 23