



| CUBE |



ICECREAM & DISPLAY FREEZER

FEATURES

- Flat solid sliding lids
- Thermometer
- Castors
- Options:
 - Baskets
 - Dividers
 - Lock
 - Graphics (minimum quantity required)
 - Castors with brake

At first sight it may look like a traditional freezer for ice cream and frozen food but furthermore we can offer very high quality and reliability.

New technologies has allowed us to use compressors with very low energy consumption, which also includes the use of hydro carbons. The lid system is unique. Once you get to the final part of the closing process, the lid is partially self-closing.



TYPICAL CONFIGURATION OF VENTILATION GRIDS



	CUBE 22	CUBE 35	CUBE 45	CUBE 53	CUBE 61
CLIMATE CLASS	B (former class 4+)	B (former class 4+)	B (former class 4+)	B (former class 4+)	B (former class 4+)
VOLUME					
Gross volume, litres	205	331	426	503	602
Net volume, litres	163	267	345	408	489
TEMPERATURE					
Ambient temperature range, deg. C	+16 to +35	+16 to +35	+16 to +35	+16 to +35	+16 to +35
Temperature range inside unit, degree C	-16 to -23	-16 to -23	-16 to -23	-16 to -23	-16 to -23
COOLING DATA					
Refrigerant	R290	R290	R290	R290	R290
Refrigerant amount, gram	66	68	80	96	112
Type of cooling	Static	Static	Static	Static	Static
Type of defrost	Manual	Manual	Manual	Manual	Manual
ENERGY					
Energy consumption / 24h kwh at 30 deg. C	1,20	1,73	1,90	2,39	3,10
AE- Annual Energy consumption, kwh	438	631	692	872	1131
EEL- Energy Efficiency Index	34,0%	38,6%	36,3%	41,1%	47,1%
EC-Energy Class	C	D	D	D	D
Input power (watt)	141	153	203	204	230
ELECTRICAL DATA					
Power	220-240 v / 50 Hz	220-240 v / 50 Hz	220-240 v / 50 Hz	220-240 v / 50 Hz	220-240 v / 50 Hz
Power 110 volt / 60 hz	Optional	Optional	Optional	Optional	Optional
Current consumption (ampere)	4	4	4	4	4
DIMENSIONS					
External dimensions (wxdxh)	764*694*867	1094*694*867	1344*694*867	1544*694*867	1804*694*867
Internal dimensions (wxdxh)	606*536*688	936*536*688	1186*536*688	1386*536*688	1646*536*688
Dimension A	764	1094	1344	1544	1804
Dimension B	694	694	694	694	694
Dimension C	867	867	867	867	867
Dimension D	764	764	764	764	764
Dimension E	606	936	1186	1386	1646
Dimension F	406	736	986	1186	1446
Dimension G	536	536	536	536	536
Dimension H	688	688	688	688	688
Dimension J	438	438	438	438	438
Dimension L	798	798	798	798	798
Insulation (mm)	77	77	77	77	77
STANDARD					
Outer cabinet	White Galv. Steel	White Galv. Steel	White Galv. Steel	White Galv. Steel	White Galv. Steel
Inner cabinet	Steel inner liner	Steel inner liner	Steel inner liner	Steel inner liner	Steel inner liner
Insulation	Polyurethane	Polyurethane	Polyurethane	Polyurethane	Polyurethane
Thermometer	Digital	Digital	Digital	Digital	Digital
Thermostat	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Castors	Inclusive	Inclusive	Inclusive	Inclusive	Inclusive
OPTIONS					
Dividers	Optional	Optional	Optional	Optional	Optional
Max number of baskets	2	3	4	5	6
Castors w brakes	Optional	Optional	Optional	Optional	Optional
Lock	Optional	Optional	Optional	Optional	Optional
Internal light	n/a	n/a	n/a	n/a	n/a
Graphics	Optional	Optional	Optional	Optional	Optional
OTHER DATA					
CE/ UL / DOE approval	CE	CE	CE	CE	CE
WEIGHT					
Net weight, kg	45	53	61	68	71
Gross weight, kg	48	57	65	72	75
SHIPPING					
20' cont. capacity	42	30	24	20	18
40' cont. capacity	84	62	50	44	38
40' HC cont. capacity	126	91	74	64	55
Standard trailer capacity	153	105	84	78	63



*) Climate class 4 has been changed into Climate class A according to the new EU regulation.
 *) Climate class 7 has been changed into Climate class B according to the new EU regulation.
 *) Climate class 5 has been changed into Climate class C according to the new EU regulation.