


FOCUS V

IDEAL FOR BULK



FOOD BUCKET
(FDA-APPROVED FOR FOOD)



DRAIN

The FOCUS V freezer has an elegant, yet robust, design to optimally catch the attention of your customers. The lid design, the improved insulation and the heated frame ensure minimum ice build-up.

Cyclopentane is used as blowing agent and the cabinets are CFC free.



FOCUS 106 V WITH BULK CONTAINER

FOCUS 106 V WITH OPEN LID

FEATURES

- Curved lift-up glass lids
- Thermometer
- Castors
- Options:
 - Baskets or plastic food buckets
 - Dividers for baskets
 - LED
 - Graphics (minimum quantity required)
 - Castors with brake

	FOCUS 73 V	FOCUS 106 V	FOCUS 131 V
CLIMATE CLASS	B (former class 4+)	B (former class 4+)	B (former class 4+)
VOLUME			
Gross volume, litres	161	270	352
Net volume, litres	113	193	254
TEMPERATURE			
Ambient temperature range (deg. C)	+16 to +35	+16 to +35	+16 to +35
Temperature range inside unit (deg. C)	-14 to -23	-14 to -23	-14 to -23
COOLING DATA			
Standard refrigerant	R290	R290	R290
Refrigerant amount (gram)	67	75	80
Type of cooling	Static	Static	Static
Type of defrost	Manual	Manual	Manual
ENERGY			
Energy consumption / 24 h kwh at 30 deg. C	1,08	1,60	1,68
AE- Annual Energy consumption, kwh	394	585	615
EEL- Energy Efficiency Index	34,60%	39,30%	37,30%
EC-Energy Class	C	D	D
Input power (watt)	141	153	203
ELECTRICAL DATA			
Power	220-240 v / 50 Hz	220-240 v / 50 Hz	220-240 v / 50 Hz
Power 110volt / 60 hz	Optional	Optional	Optional
Current consumption (amperes)	4	4	4
DIMENSIONS			
External dimensions (wxdxh)	726*656*878	1056*656*878	1306*656*878
Internal dimensions (wxdxh)	570*500*670	900*500*670	1150*500*670
Dimension A	726	1056	1306
Dimension B	656	656	656
Dimension C	890	890	890
Dimension D	570	900	1150
Dimension E	370	700	950
Dimension F	500	500	500
Dimension G	725	725	725
Dimension H	475	475	475
Dimension I	770	770	770
Insulation (mm)	75	75	75
STANDARD			
Outer cabinet	White Galv. Steel	White Galv. Steel	White Galv. Steel
Inner cabinet	Aluminium	Aluminium	Aluminium
Insulation	Polyurethane	Polyurethane	Polyurethane
Thermometer	Digital	Digital	Digital
Thermostat	Mechanical	Mechanical	Mechanical
Castors	Incl.	Incl.	Incl.
OPTIONS			
Container for bulk food	2 pcs	3 pcs	4 pcs
Max number of baskets (narrow)	3	4	6
Max number of baskets (wide)	2	4	5
Dividers	Optional	Optional	Optional
Castors w. brakes	Optional	Optional	Optional
Lock	Optional	Optional	Optional
Internal light	Optional	Optional	Optional
Graphics	Optional	Optional	Optional
OTHER DATA			
UL approval / DOE approval	Yes	Yes	Yes
WEIGHT			
Net weight, kg	44	54	62
Gross weight, kg	47	58	66
SHIPPING			
20' cont. Capacity	42	30	24
40' cont. Capacity	90	64	50
40' HC cont. Capacity	126	88	62
Standard Trailer capacity	153	108	90

*) Climate class 4 has been changed into Climate class A according to the new EU regulation.

*) Climate class 7 has been changed into Climate class B according to the new EU regulation.

*) Climate class 5 has been changed into Climate class C according to the new EU regulation.